

# IBM LTO Ultrium 7 data cartridge

High-capacity tape media designed for reliability and longevity

#### Highlights

- · Achieve increased capacity
- Ensure optimal data security
- Support IBM Spectrum Archive
- Meet stringent Linear Tape-Open (LTO) Ultrium Generation 7 specifications
- Choose between rewritable and write-once-read-many (WORM) models
- Use custom, blank and RFID-embedded cartridge labels

#### Overview

With volumes of data growing exponentially—and no end in sight—the IBM LTO Ultrium 7 data cartridge is designed to help organizations protect and preserve more data for longer periods of time. This latest generation of the IBM solution offers more than double the storage capacity of previous generations for long-term data preservation that provides security as it sustains rapid, reliable access to data and helps ensure business resilience.

## **Increased capacity**

Rapid data growth compounds the need for increased storage capacity. The seventh generation of LTO Ultrium tape media delivers 6 TB native capacity and up to 15 TB of compressed capacity for significantly greater efficiency and performance. This exceptional capacity helps reduce the number of cartridges and the amount of equipment, space and labor associated with tape-based data storage.

#### **Optimal data security**

To comply with regulatory requirements and preserve stakeholder trust, organizations must protect data from unauthorized access and unintentional loss. Tape cartridge portability facilitates remote, offline data storage for superior protection from natural or manmade threats that can impact online or on-site data storage. IBM LTO Ultrium 7 data cartridges are compatible with LTO Ultrium 7 tape drives, which offer device-level data encryption to ensure data



privacy and reduce the risk of data corruption due to virus or sabotage. The WORM cartridge model stores data in a non-erasable, non-rewritable format to prevent overwriting of stored data and reduce the risk of data loss due to human error.

### **IBM Spectrum Archive support**

LTO Ultrium 7 supports tape partitioning and IBM Spectrum Archive, which features IBM Linear Tape File System technology, making tape storage an even more compelling solution for the long-term preservation of data. With IBM Spectrum Archive, the data files are indexed to facilitate search and retrieval using disk-like directory tree structures and drag-and-drop techniques to improve the usability of tape solutions. IBM Spectrum Archive allows users and applications to directly retrieve files from tape rather than rely on proprietary, third-party applications, thereby significantly enhancing data access and potentially reducing software licensing costs and dependencies.



#### IBM LTO Ultrium 7 data cartridge at a glance

| 0 m (3,149 ft)  2.0 mm x 105.0 mm x 21.0 mm (4.0 in. x 4.1 in. x 0.8 in.)  0 g (0.441 lb)  5 g (0.254 lb)  xicity: nonhazardous to human health in anticipated use mmability: self-extinguishing per UL94  °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb eximum |
|--|
| 0 g (0.441 lb) 5 g (0.254 lb)  xicity: nonhazardous to human health in anticipated use mmability: self-extinguishing per UL94  °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb  |
| 0 g (0.441 lb) 5 g (0.254 lb)  xicity: nonhazardous to human health in anticipated use mmability: self-extinguishing per UL94  °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb  |
| 5 g (0.254 lb)  xicity: nonhazardous to human health in anticipated use mmability: self-extinguishing per UL94  °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb   |
| xicity: nonhazardous to human health in anticipated use mmability: self-extinguishing per UL94  °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum  °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb   |
| °C - 45°C (50°F - 113°F); 10% - 80% RH; 26°C (79°F) wet bulb eximum °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb   |
| °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb   |
| °C - 35°C (61°F - 95°F); 20% - 80% RH; 26°C (79°F) wet bulb eximum °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb   |
| °C - 25°C (61°F - 77°F); 20% - 50% RH; 26°C (79°F) wet bulb  |
|  |
|  |
| 3°C - 49°C (-9°F - 120°F); 20% - 80% RH; 26°C (79°F) wet bulb<br>ix  |
| assified as nonhazardous waste per EPA regulation 40CFR261;<br>n be disposed of as normal office trash   |
|  |
| 89-651 (p/n 38L7302)   |
| 89-671 (p/n 38L7303)   |
| 89-004 (p/n 35L2086)   |
| ee from defects in manufacturing and materials defects for the eful life of the product  |
| 8  |



### Why IBM?

LTO is an open tape architecture developed by a consortium of world-class storage producers. Compatible LTO tape drives and media are available from multiple vendors. Purchasing LTO Ultrium 7 data cartridges from IBM provides peace of mind in sourcing media from a trusted, time-proven tape technology leader.

#### For more information

To learn more about the IBM LTO Ultrium 7 data cartridge, please contact your IBM representative or IBM Business Partner, or visit: **ibm.com**/systems/storage/media. You may also contact 1-888-IBM-MEDIA (1-888-426-6334).

Additionally, IBM Global Financing provides numerous payment options to help you acquire the technology you need to grow your business. We provide full lifecycle management of IT products and services, from acquisition to disposition. For more information, visit: ibm.com/financing





# Systems Hardware Data Sheet



© Copyright IBM Corporation 2019.

IBM, the IBM logo, and ibm.com are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at

https://www.ibm.com/legal/us/en/copytrade.shtml, and select third party trademarks that might be referenced in this document is available at https://www.ibm.com/legal/us/en/copytrade.shtml#se ction\_4.

This document contains information pertaining to the following IBM products which are trademarks and/or registered trademarks of IBM Corporation:  $IBM \circledast, IBM \text{ Spectrum Archive}^{\mathsf{TM}}, IBM \text{ Linear Tape File System}^{\mathsf{TM}}$ 

## IBM.

Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium Logo are registered trademarks of Hewlett Packard Enterprise, International Business Machines Corporation and Quantum Corporation in the United States and other countries.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.